## Quantities and Specifications of IT items to be purchased

Sl.Na	Non-Govt. Aided Colleges	Nos of College	Amount to be released (in lakhs)	Detail calculation	Total Amount (in lakhs)
1	No of No Govt. Aided Colleges having student's strength more than 750	199	8	1.I3 and above Desktop @50000*12=6 Lakh 2. UPS@3000*12=36000 lakh 3. MFM Printer@30000 *2=60000 4.1 LED Tv (65 inch) @0.70= 70000 5. Wireless mice &Camera for Virtual meeting = 25000 6. Internet Facility:-20,000/- Total=8.11 Lakh	1592
	No of Non-Govt. Aided Colleges having student's strength less than 750	449	4.5	1.I3 and above Desktop @50000*6=3.0 Lakh 2. UPS@3000*6=18000 t 3. MFM Printer@30000*2=0.60 Lakh 4.1 LED Tv(65 inch)@70000=.70 Lakh 5.Wire less Mice & Camera with MIC for Virtual meeting = 25000 6. Internet facility=20000 Total=4.93 Lakh	2020.5
		648			3612.5

Cabinet Form Form	p Specification	
Chipset Number	Tower/Micro Tower (15	
Processor Make	Tower/Micro Tower (15.1 to 26 Litres)	
Processor	Intel H670/Intel® H770 or higher Chipset	
Processor Generation	x86 64-bit architecture	
Processor Description	13 Or higher	
Processor Number	Intel Core i3 or higher	
Number of Cores and The	Intel Core i3 13100 or higher	
Number of Cores and Threads per Processor	Max Turbo Frequency 4 5Ghz Main	
Operating System		
RAM Size (GB)	Windows 11 Home Factory Preloaded	
RAM Expandability up to (using spare DIMM Slots in GB) Integrated Graphics	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
- Comments	of GB of nigher	
Supported for discrete NVIDIA/AMD Graphics Card up to	Intel UHD Graphics 770 or higher	
	Yes	
Type of Drives used to populate the Internal Bays	NVMe SSD	
Total HDD Capacity (GB)	NA NA	
Total SSD Capacity (GB)	512GB NVMe SSD	
Optical Drive	Optional Optional	
Drive Bays	Two 3.5" (2.5") HDD	
The second secon	1 PCI Express 4.0 x16,	
Slots for Upgradation	1 PCI Express 3.0 x1,	
	1 PCI (Full Height),	
LAN	2 M.2 slots for WLAN & SSD	
	LAN: Integrated 10/100/1000M	
The state of the s	Front: 1 headphone/microphone combo; 3 Super Speed SGbps signalling rate: 2 Super Speed USB 10 Charles	
Ports and Connectors	5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalli rate; 1 USB Type-C, total 6nos USB in front for easy acces	
THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COL	Rear: I HDMI; I Serial Port; I line in; I line out: I power	
Firmware Trusted Platform Module	connector; 1 RJ-45; 1 DP; 2 USB 2.0	
Hardware Security lock slot	TPM 2.0	
Total Personal Processing Total Stock	Security lock slot	
Power Supply	180-260Watt Internal power supply with minimum 90% efficiency	
	Bidder should submit OEM bid specific authorization & th	
	same authorization may be verified by the respective OEA	
	required.	
	OEM must have the ISO 9001,14001, ISO 20001, ISO 2700 Certificate	
ertification	Microsoft Windows, Energy star 8.0 certified	
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate	
the Continue of the Continue o	products at the time of participation of the Bid.	
	USB Keyboard; USB Optical Mouse	
Monitor	19.5" LED Display with CTO Certified and same must be	
	belongs to the same OEM	
	3 Year Onsite Warranty	

SI. No	. Feature 600 VA Line	Interactive UPS Specifications	
1	UPS Capacity (total)	General Specifications	
2	Input Voltage	600VA/360W	
3	Input Frequency	230 VAC nominal	
4	Brownout Transfer	45 - 65 Hz	
5	Over-voltage Transfer	145 VAC typical	
6		290 VAC typical	
0	Voltage on Battery		
7	Francisco	230 VAC typical (stepped approximated sine wave)	
8	Frequency - On Battery Transfer Time	50Hz typical	
	manister time	@50 Hz 6 ms typical, 10 ms max	
9	Air Ventilation		
		Should have Side and Back Honey bee Perforation for headispersion	
10	Protection from Humidity & Dust		
		UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity	
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of th	
		Battery upto 5 years	
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
13	AC Surge Protection	Full time, 160 joules	
14	Automatic Re start of UPS		
	2007073	In case the UPS backup is totally drained and automatic	
		switched off, when the grid power resumes the UPS Shoul	
15	Type (maintenance-free)	Auto Start without human interference. 12V, 7.2 Ah	
	Typical recharge time	4- 6 hours	
VICEOUS HOUSE	Operating Temperature	0°C to 40°C	
18	Storage Temperature	-15°C to 45°C	
19	3 power outlets	With battery backup and surge protection	
20	Power Cord 1.2 meters		
21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)	
	intime for Workstation PC (100W ±15W) 13 min (normal mode)		
23 E	Battery Saver (to save on battery life)	Thru toggle button on front panel	
24 (	Certification	BIS	
25 [	Designed and Manufactured in India	Yes	
26 V	Warranty	2 years	

.

Description of Stores	Generic	
	Multifunction Machine Delete	
	Warranty, including Cartridge and Power Cord/Adapter	
Core Function	and rower Cord/Adapter	
Print Technology	Print, Scan and Copy	
Cartridge Technology	Laser	
Type of Printing	Composite Cartridge	
RAM Size (MB)	Monochrome (Black)	
Storage Capacity (in GB)	256	
capacity (in GB)	0	
Features		
Operating System Compatibility	Fax	
. Same System Compatibility	Windows 10 and Above, Linux, Mac OS, Windows Server	
Print Paper Size	Printing A4 and Legal	
Minimum Print Speed per	26 to 30	
Minute as per ISO/IEC 24734 in	20.000	
A4 Size-Monochrome (Black)		
(in PPM)		
Minimum Print Speed per	Not Applicable	
Minute as per ISO/IEC 24734 in		
A4 Size-Colour (in PPM)		
Minimum Speed per Minute as	Not Applicable	
per ISO/IEC 24734 in A3 Size-		
Mono (in PPM)		
Minimum Speed per Minute as	Not Applicable	
per ISO/IEC 24734 in A3 Size-		
Color (in PPM)		
Auto Duplexing Printing/Coping	Yes	
(2-sided Feature)		
	Scanning	
Maximum Scan Area	A4 and Legal	
(Platen/Flatbed Size)	7.1.4.14.14.14.14.14.14.14.14.14.14.14.14	
A4 Scan Speed -Colour (Image	11 to 20	
Per Minute) @ 300 x 300 dpi		
0. Milloto) @ 000 x 000 upi		
Scan To Functions	Email	
A4 Scan Speed - Mono (Image	11 to 20	
Per Minute) @ 300 x 300 dpi		
The state of the s		
	COPYING	
Reduction and Enlargement	Yes	
eature	and the second s	

	PAPER HANDLING
Original Document Feeder Type	
(For Scanning and Copying)	Automatic Document Feeders (ADF)
,,9	Coders (ADF)
Feeder Capacity (Number of Sheets) (For See	
Sheets) (For Scanning and	31 to 40
copying)	
Number of Main Paper Tray	
	1
Total Paper Tray Combined	101 to 200
oapacity (Number) at 75 GSM	101 to 200
Bypass Tray Facility	No
If Yes, Bypass Tray Capacity	0
Connectivity	
Connectivity	USB Port,Ethernet Port,Wi-Fi
Accessories Provided	USB Cable
V:	Performance
Minimum Yield of the	700
Cartridge/Ink/Toner supplied	
with Machine as per IS/ISO/IEC:	
19752/2017 for Black (Number	
of Prints)	
Minimum Yield of the	
Cartridge/Ink/Toner Supplied	0
with Machine as per IS/ISO/IEC:	
19798:2017 for Cyan, Yellow	
and Magenta Color (Number of	
Prints)	
Minimum Duty Cycle (Number	10,001 to 20,000
of Prints/Month)	
Power Supply	POWER
V	Single Phase AC 220 - 240 V, 50 - 60 Hz
(in Watt)	1300
vironmental	
	10
emperature (Degree C)	
aximum Operating 3	00
emperature (Degree C)	

Minimum Operating Humidity (%RH)	20
Maximum Operating Humidity (%RH)	80
	Dimension
Standard Machine Weight with Single Tray (in Kg)	11
	Certification
BIS CRS Compliance	Yes as per IS 13252 (Part 1)
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes

		P. H. L. St. St. St. St. St. St. St. St. St. St
	Screen Size	65
	Brightness (cd/m³)	350Nits or better
General Features	Contrast Ratio	1200:1
reatures	Dynamic Contrast Ratio	400,000:1
	Response Time (ms)	8.0
	Display resolution (H x V, pixels)	3840 × 2160
	HDR (High Dynamic Range) compatiblity	Yes (HDR10, HLG)
	Aspect Ratio	16:9 Yes
	Portrait/Tilt Compatibility	Frame Dimming
	Dimming type	Frame Diffining
	Display Device	IPS
	Panel Type	Direct LED
Display features	Backlight type	69%
- Colles	Color gamut (NTSC)	16/7
	Operation time	1%
	Haze (%)	178 (89/89) degree
	Viewing Angle (Right/Left)	178 (89/89) degree
	Viewing Angle (Up/Down)	178 (89/85) 008
	HDMI Signal	4096 x 2160p (24, 50, 60 Hz), 3840 x 2160p (24, 25, 30, 50, 60 Hz), 1080p (30, 50, 60 Hz), 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
		Down Firing
Audio Specs	Speaker Position	10W + 10W
TANKS OF STREET	Audio Power Output	Yes (Simple Pro settings menu
Deafassian J	Pro settings	Yes (Simple F10 300)
Professional	HDMI auto wake-up	Android TV
features	Operating System	
	On-board Storage (GB)	16GB
	RAM	3GB
	Wi-Fi Certified	Yes
etwork Specs		Integrated
	Wireless LAN  USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
onvenience	On Screen Clock	Yes
	Sleep Timer	Yes
features		Yes
The state of the s	On/Off Timer	Yes
	Chromecast built-in	
	Apple AirPlay	Yes
	IP Control	Yes
ntrol Specs	RS-232C Control	Yes
III(IOI Specs	HDMI-CEC	Yes
	HDCP	
		HDCP2.3 (for HDMI1/2/3
	Composite Video Input (s)	1 (Side, Mini jack)

ı

/	HDMI inputs total	
Inputs and outputs	Analog Audio Input (s) (Total)	3 (3Side)
	Digital Audio Output (s)	1 (Side Analog Conversion)
	USB ports	1 (Side)
	Ethernet inputs	2 (Side)
Design features	VESA* Hole Pitch (W x H)	1 (Side)
		300 x 300 mm
	Rated Power Consumption	226W
Environment Specs	Power Consumption (in Standby)	0.5 W
	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
	Weight of TV without Stand	20.4 kg
Weight	Weight of TV with Stand	21.3 kg
	Weight of Package Carton (Gross)	28 kg